

Specification Sheet - 2023-3

90DEG Liquidtight Connectors

LT and LTI-series liquidtight connectors are used to connect metallic liquidtight conduit to a box or enclosure. The total product line offers reliable and durable connection which will stand up to corrosive and wet locations.

East Electric 90 degree liquidtight connectors are suitable for metallic and nonmetallic type B liquidtight and used to seal out water, oil & dust and other damaging particles to ensure continued product integrity and performance. Available for 3/8" – 4". Zinc - UL Listed

Features

- CUL) US
- Hex surface on gland nut for easy wrenching to save installation time
- Thermoplastic sealing rings
- Cupped long ferrule with maximum contact surface provides metal to metal contact with conduits for safe grounding

	90DEG	Liquidtight Connecto	ors	
	Part No.	Size	Inner Case	Master Case
	LT90-38	3/8"	10	100
	LT90-50	1/2"	10	100
	LT90-75	3/4"	10	100
	LT90-100	1"	5	50
	LT90-125	1 1/4"	2	20
	LT90-150	1 1/2"	2	20
	LT90-200	2"	N/A	10
	LT90-250	2 1/2"	N/A	1
	LT90-300	3"	N/A	1
	LT90-400	4"	N/A	1
Certifications: UL-514B				