

Specification Sheet - 2023-3

## **Raintight Compression Connectors**

Assembled with sealing ring and knockout gasket, compression-style connector can provide a raintight seal when connecting EMT to a box or enclosure. Zinc-plated steel. Concrete-tight, raintight.

East Electric Steel EMT Raintight Connectors are UL listed for WET LOCATIONS and used to join EMT conduit to a box or enclosure. Zinc Plated Steel, UL Listes, NEMA/ANSI FB-1 compliant.

## **Features**

- Hex on the gland nut creates a flat, smooth surface for convenient wrenching
- Installation is safe and sealed by using integral gasket compression ring
- Interior shoulder conduit stop provides positive seating of conduit inside the body
- Gasket on male threads of box connector makes raintight connection between box and connector
- Optional insulator made of high-performance thermoplastic available
- Angled teeth on the locknut securely bite into enclosure

## **Standard Materials**



- Body/Compression Nut/Locknut: Zinc-plated steel
- Gasket/Sealing Rings: Thermoplastic

| Raintight Compression Connectors |            |        |            |             |
|----------------------------------|------------|--------|------------|-------------|
|                                  | Part No.   | Size   | Inner Case | Master Case |
|                                  | CC-50RTS1  | 1/2"   | 25         | 250         |
|                                  | CC-75RTS1  | 3/4"   | 25         | 250         |
|                                  | CC-100RTS1 | 1"     | 10         | 100         |
|                                  | CC-125RTS1 | 1 1/4" | N/A        | 25          |
|                                  | CC-150RTS1 | 1 1/2" | N/A        | 20          |
|                                  | CC-200RTS1 | 2"     | N/A        | 15          |
|                                  | CC-250RTS1 | 2 1/2" | N/A        | 12          |
|                                  | CC-300RTS1 | 3"     | N/A        | 12          |
|                                  | CC-350RTS1 | 3 1/2" | N/A        | 5           |
|                                  | CC-400RTS1 | 4"     | N/A        | 3           |
| Certifications: UL-514B          |            |        |            |             |