



# East Electrical Supply Inc.

Specification Sheet - 2023-7

## Liquidtight Conduit Coils

For use in damp or wet locations, suitable for commercial and industrial use Non-UL

### Features

- Crush and corrosion resistant steel core for lasting mechanical protection
- EF PVC jacket is oil and sunlight resistant
- Smooth interior for easy wire pull through

### Standard Materials

- EF PVC jacketed steel core coil wrapped in clear plastic shrink wrap



### Liquidtight Conduit Coils

Part No.	Size	Length (ft.)
LTMCM-38100	3/8"	100
LTMCM-50100	1/2"	100
LTMCM-75100	3/4"	100
LTMCM-100100	1"	100
LTMCM-12550	1 1/4"	50
LTMCM-15050	1 1/2"	50
LTMCM-20025	2"	25
LTMCM-20050	2"	50
LTMCM-25025	2 1/2"	25
LTMCM-30025	3"	25
LTMCM-35025	3 1/2"	25
LTMCM-40025	4"	25

### Outside Diameter

Min	Max
0.689	0.709
0.819	0.839
1.032	1.051
1.287	1.315
1.630	1.661
1.866	1.902
2.339	2.374
2.339	2.374
2.839	2.874
3.461	3.500
3.960	4.000
4.457	4.500

### Inner Diameter

Min	Max
0.484	0.504
0.622	0.642
0.815	0.835
1.032	1.055
1.370	1.394
1.579	1.598
2.020	2.043
2.020	2.042
2.480	2.504
3.071	3.102
3.500	3.540
4.000	4.039