


EAST ELECTRICAL SUPPLY INC

Specification Sheet - 2025-2

Saddle Connectors

Used to connect armored or metal-clad cable to a box or enclosure.

| Saddle Connectors | | | |
|---|------------|------|-----------------|
| | Partno | Size | Master Case Qty |
|  | MC-SAD-38S | 3/8" | 500 |
| | BL-17 | 1/2" | 200 |
| | BL-18 | 3/4" | 200 |
| | BL-19 | 1" | 100 |

| Cable Type | Cable Size | Cable Diameter |
|-----------------------------------|-------------|----------------|
| Armored Cable, Steel | 14/2 – 8/2 | 0.475-0.650 |
| Armored Cable, Aluminum | 14/2 – 8/2 | 0.464-0.665 |
| HCF Armored Cable, Steel | 14/2 – 8/2 | 0.475-0.650 |
| HCF Armored Cable, Aluminum | 14/2 – 8/2 | 0.464-0.665 |
| Metal Clad Cable, MCI, Steel | 14/2 – 10/4 | 0.455-0.625 |
| Metal Clad Cable, MCI, Aluminum | 14/2 – 10/4 | 0.455-0.625 |
| Metal Clad Cable, MCI-A, Aluminum | 14/2 – 10/4 | 0.385-0.565 |
| HCF MCI-A | 14/2 – 10/4 | 0.385-0.565 |
| FMC/RWFMC/XRWFMC, Steel | 3/8 | - |
| FMC/RWFMC/XRWFMC, Aluminum | 3/8 | - |
| NM cable | 14/2 – 12/3 | - |
| MC-PCS | 12-2 - 12-3 | 0.529-0.610 |

