



## 1/2" Thru 1" Rigid Nipples

Rigid nipples are used to extend a length of threaded rigid or IMC conduit.

Rigid conduit nipple is manufactured from high-strength steel according to the latest ANSI specifications. The nipples are free from defect, and evenly coated with zinc during the hot dip galvanizing process. Nipples are produced in normal trade sizes from 1/2" to 6", with lengths from CLOSE, 1 1/2" up to 12".

### Features

- NPT Thread
- Hot-dip galvanized for corrosion resistance



### 1/2" Thru 1" Rigid Nipples



Part No.	Size	Inner Case	Master Case
012CGRN	1/2" X CLOSE	25	600
012GRN150	1/2" X 1 1/2"	25	600
012GRN200	1/2" X 2"	25	600
012GRN250	1/2" X 2 1/2"	25	400
012GRN300	1/2" X 3"	25	400
012GRN400	1/2" X 4"	25	300
012GRN500	1/2" X 5"	25	200
012GRN600	1/2" X 6"	25	200
034CGRN	3/4" X CLOSE	25	400
034GRN200	3/4" X 2"	25	400
034GRN250	3/4" X 2 1/2"	25	300
034GRN300	3/4" X 3"	25	200
034GRN400	3/4" X 4"	25	150
034GRN500	3/4" X 5"	25	100
034GRN600	3/4" X 6"	25	100
100CGRN	1" X CLOSE	25	300
100GRN200	1" X 2"	25	200
100GRN250	1" X 2 1/2"	25	200
100GRN300	1" X 3"	25	150
100GRN400	1" X 4"	25	100
100GRN500	1" X 5"	25	100
100GRN600	1" X 6"	25	75

**Certifications: E533064**