



# East Electrical Supply Inc.

Specification Sheet - 2023-6

## 1 1/4" Thru 2" Rigid Nipples

Rigid nipples are used to extend a length of threaded rigid or IMC conduit.

Rigid conduit nipple is manufactured from high-strength steel according to the latest ANSI specifications. The nipples are free from defect, and evenly coated with zinc during the hot dip galvanizing process. Nipples are produced in normal trade sizes from 1/2" to 6", with lengths from CLOSE, 1 1/2" up to 12".

### Features

- NPT Thread
- Hot-dip galvanized for corrosion resistance



### 1 1/4" Thru 2" Rigid Nipples

Part No.	Size	Inner Case	Master Case
125CGRN	1 1/4" X CLOSE	25	150
125GRN200	1 1/4" X 2"	25	150
125GRN300	1 1/4" X 3"	25	100
125GRN400	1 1/4" X 4"	25	100
125GRN500	1 1/4" X 5"	25	75
125GRN600	1 1/4" X 6"	25	50
150CGRN	1 1/2" X CLOSE	25	100
150GRN200	1 1/2" X 2"	25	75
150GRN250	1 1/2" X 2 1/2"	25	75
150GRN300	1 1/2" X 3"	25	100
150GRN400	1 1/2" X 4"	25	50
150GRN500	1 1/2" X 5"	25	50
150GRN600	1 1/2" X 6"	25	50
200CGRN	2" X CLOSE	25	75
200GRN250	2" X 2 1/2"	N/A	50
200GRN300	2" X 3"	N/A	50
200GRN400	2" X 4"	N/A	40
200GRN500	2" X 5"	N/A	40
200GRN600	2" X 6"	N/A	30

**Certifications: E533064**