



2 1/2" Thru 4" Rigid Nipples

Rigid nipples are used to extend a length of threaded rigid or IMC conduit.

Rigid conduit nipple is manufactured from high-strength steel according to the latest ANSI specifications. The nipples are free from defect, and evenly coated with zinc during the hot dip galvanizing process. Nipples are produced in normal trade sizes from 1/2" to 6", with lengths from CLOSE, 1 1/2" up to 12".

Features

- NPT Thread
- Hot-dip galvanized for corrosion resistance



2 1/2" Thru 4" Rigid Nipples



| Part No. | Size | Inner Case | Master Case |
|-----------|----------------|------------|-------------|
| 250CGRN | 2 1/2" X CLOSE | N/A | 40 |
| 250GRN300 | 2 1/2" X 3" | N/A | 40 |
| 250GRN400 | 2 1/2" X 4" | N/A | 30 |
| 250GRN500 | 2 1/2" X 5" | N/A | 20 |
| 250GRN600 | 2 1/2" X 6" | N/A | 20 |
| 300CGRN | 3" X CLOSE | N/A | 30 |
| 300GRN400 | 3" X 4" | N/A | 15 |
| 300GRN500 | 3" X 5" | N/A | 15 |
| 300GRN600 | 3" X 6" | N/A | 10 |
| 400CGRN | 4" X CLOSE | N/A | 20 |
| 400GRN400 | 4" X 4" | N/A | 10 |
| 400GRN500 | 4" X 5" | N/A | 8 |
| 400GRN600 | 4" X 6" | N/A | 8 |

Certifications: E533064