



UL Flexible Aluminum Conduit Reels

For use as an electrical raceway in close quarters requiring extra flexibility; one-third the weight of steel.


Features

- Corrosion resistant
- Lightweight, easy to cut
- Smooth interior for easy wire pull through
- Easy to follow contours
- Crush resistant
- UL Listed

Standard Materials

- Aluminum alloy construction, with tempered allow for maximum strength



| UL Flexible Aluminum Conduit Reels | | | | |
|------------------------------------------------------------------------------------|------------|--------|------------|-------------|
| | Part No. | Size | Inner Case | Master Case |
|  | RWA-501000 | 1/2" | N/A | 1000 |
| | RWA-75500 | 3/4" | N/A | 500 |
| | RWA-100300 | 1" | N/A | 300 |
| | RWA-125200 | 1 1/4" | N/A | 200 |
| | RWA-150100 | 1 1/2" | N/A | 100 |
| | RWA-200100 | 2" | N/A | 100 |

| Inner Diameter | | Outside Diameter | |
|----------------|-------|------------------|-------|
| Min | Max | Min | Max |
| 0.625 | 0.644 | 0.859 | 0.920 |
| 0.811 | 0.835 | 1.044 | 1.105 |
| 1.000 | 1.040 | 1.300 | 1.379 |
| 1.250 | 1.300 | 1.550 | 1.629 |
| 1.500 | 1.573 | 1.850 | 1.950 |
| 2.000 | 2.079 | 2.350 | 2.450 |