EAST ELECTRICAL SUPPLY INC

Specification Sheet - 2025-2

Malleable Iron Liquidtight Insulated Connector - 45DEG

To secure, ground and seal liquidtight conduit to a box or enclosure UL listed liquidtight flexible metal conduit fittings are suitable for use in the following hazardous locations under: NEC 501-4(b), 502-4(a), (2)503-3(a) Class 1 Div.2, Class II Div.1 and 2, Class III Div.1 and 2 and are suitable for grounding in sizes 3/8" through 1-1/2" under NEC 351-I

Features

- Liquidtight, raintight, oiltight
- Suitable for wet location use
- Tapered threaded male hub NPT
- Insulated throat protects conductors from abrasion damage
- Compact slim diameter with small turning radius
- Zinc electro plated for excellent durability

Standard Materials

- Malleable Iron
- Steel Locknut

Malleable Iron Liquidtight Insulated Connector - 45DEG

Partno	Size	Item Description	Inner Case Qty	Master Case Qty
230S	3/8"	3/8" 45 DEGREE MALL IRON LIQ TIGHT CONN - INS -10/100	10	100
231S	1/2"	1/2" 45 DEGREE MALL IRON LIQ TIGHT CONN - INS -10/100	10	100
232S	3/4"	3/4" 45 DEGREE MALL IRON LIQ TIGHT CONN - INS -10/100	10	100
233S	1"	1" 45 DEGREE MALL IRON LIQ TIGHT CONN - INS -10/100	10	100
234S	1 1/4"	1-1/4" 45 DEGREE MALL IRON LIQ TIGHT CONN - INS -2/20	2	20
235S	1 1/2"	1-1/2" 45 DEGREE MALL IRON LIQ TIGHT CONN - INS -2/20	2	20
236S	2"	2" 45 DEGREE MALL IRON LIQ TIGHT CONN - INS -2/20	2	20
237S	2 1/2"	2-1/2" 45 DEGREE MALL IRON LIQ TIGHT CONN - INS -1PK	N/A	1
238S	3"	3" 45 DEGREE MALL IRON LIQ TIGHT CONN - INS -1PK	N/A	1
239S	3 1/2"	3 1/2" 45 DEGREE MALL IRON LIQ TIGHT CONN - INS -1PK	N/A	1
240S	4"	4" 45 DEGREE MALL IRON LIQ TIGHT CONN - INS -1PK	N/A	1

c UL us LISTED

© 2025 East Electrical Supply