EAST ELECTRICAL SUPPLY INC

Specification Sheet - 2025-2

# Insulated Metallic Grounding Bushings - Malleable Iron

Indoor or outdoor use (aluminum lug). Use with locknut to terminate service conduit to a cabinet. Lug provided for bonding jumper to a neutral bus bar. Round surface of bushing prevents damage to wire insulation. Plastic liner prevents damage to wire insulation .

## Features

- Liner is rated flame retardant to 105°C
- UL listed for use with copper or aluminum grounding conductor

## Standard Materials

- Body - Malleable iron
- Plastic insulator
- Lug - Aluminum
- Clamping screw - Steel
- Set screws - Steel

**Insulated Metallic Grounding Bushings - Malleable Iron**

| Partno | Size | Item Description | Master Case Qty |
|---|---|---|---|
| 331M | 1/2" | 1/2" Malleable Iron Insulated Ground Bushing with 14-4 AL Lug | 500 |
| 332M | 3/4" | 3/4" Malleable Iron Insulated Ground Bushing with 14-4 AL Lug | 500 |
| 333M | 1" | 1" Malleable Iron Insulated Ground Bushing with 14-4 AL Lug | 250 |
| 334M | 1-1/4" | 1-1/4" Malleable Iron Insulated Ground Bushing with 14-4 AL Lug | 200 |
| 335M | 1-1/2" | 1-1/2" Malleable Iron Insulated Ground Bushing with 14-4 AL Lug | 100 |
| 336M | 2" | 2" Malleable Iron Insulated Ground Bushing with 14-4 AL Lug | 100 |
| 337M | 2-1/2" | 2-1/2" Malleable Iron Insulated Ground Bushing with 14-1/0 AL Lug | 10 |
| 338M | 3" | 3" Malleable Iron Insulated Ground Bushing with 14-1/0 AL Lug | 10 |
| 339M | 3-1/2" | 3-1/2" Malleable Iron Insulated Ground Bushing with 14-1/0 AL Lug | 10 |
| 340M | 4" | 4" Malleable Iron Insulated Ground Bushing with 14-1/0 AL Lug | 10 |
| 340AM | 5" | 5" Malleable Iron Insulated Ground Bushing with 6-250 AL Lug | 10 |
| 340BM | 6" | 6" Malleable Iron Insulated Ground Bushing with 6-250 AL Lug | 10 |

c UL us LISTED

© 2025 East Electrical Supply