

Specification Sheet - 2023-3

## **3PC Rigid Couplings**

Used to join two lengths of threaded conduit or IMC when neither can be rotated.

East Electrical three-piece rigid couplings ensure mechanical protection and a secure connection of Rigid or IMC conduit. Sizes available from 1/2" to 4"; UL approved.

Material - Zinc Plated, Malleable Iron

## **3PC Couplings**



|                         | Part No. | Size   | Inner Case | Master Case |
|-------------------------|----------|--------|------------|-------------|
|                         | R3K-50M  | 1/2"   | 20         | 200         |
|                         | R3K-75M  | 3/4"   | 10         | 100         |
|                         | R3K-100M | 1"     | 5          | 50          |
|                         | R3K-125M | 1 1/4" | 5          | 50          |
|                         | R3K-150M | 1 1/2" | 3          | 30          |
|                         | R3K-200M | 2"     | N/A        | 20          |
|                         | R3K-250M | 2 1/2" | N/A        | 10          |
|                         | R3K-300M | 3"     | N/A        | 5           |
|                         | R3K-350M | 3 1/2" | N/A        | 5           |
|                         | R3K-400M | 4"     | N/A        | 2           |
|                         |          |        |            |             |
| Certifications: UL-514B |          |        |            |             |