



45DEG Rigid Elbows

For a secure connection to Rigid conduit; bend enables directional changes in conduit


Features


- Low conductivity, high corrosion resistance
- Smooth, defect-free interior and exterior

Standard Materials

- Galvanized Steel



45DEG Rigid Elbows				
	Part No.	Size	Inner Case	Master Case
	012RE45	1/2" x 45°	N/A	50
	034RE45	3/4" x 45°	N/A	50
	100RE45	1" x 45°	N/A	35
	125RE45	1 1/4" x 45°	N/A	30
	150RE45	1 1/2" x 45°	N/A	15
	200RE45	2" x 45°	N/A	15
	250RE45	2 1/2" x 45°	1	50
	300RE45	3" x 45°	1	40
	400RE45	4" x 45°	1	35
	Certifications: E533064			

	(A) Min. UL Radius, inches	(B) Straight Leg Each End, inches	(C) Offset, inches
	4	1.87	2.52
	4.5	2.11	2.83
	5.75	2.26	3.35
	7.25	2.76	4.02
	8.25	3.25	4.72
	9.5	4.29	5.83
	10.5	5.12	6.69
	13	6.14	8.15
	15	6.73	9.17
	16	7.09	9.69
	24	11.06	14.92
	30	12.72	17.8