



## UL Flexible Aluminum Conduit Coils

For use as an electrical raceway in close quarters requiring extra flexibility; one-third the weight of steel.


### Features

- Corrosion resistant
- Lightweight, easy to cut
- Smooth interior for easy wire pull through
- Easy to follow contours
- Crush resistant
- UL Listed

### Standard Materials

- Aluminum alloy construction, with tempered allow for maximum strength



UL Flexible Aluminum Conduit Coils			
	Part No.	Size	Length (ft.)
	RWA-38100	3/8"	100
	RWA-38250	3/8"	250
	RWA-50100	1/2"	100
	RWA-75100	3/4"	100
	RWA-10050	1"	50
	RWA-12550	1 1/4"	50
	RWA-15025	1 1/2"	25
	RWA-20025	2"	25
	RWA-25025	2 1/2"	25
	RWA-30025	3"	25
	RWA-35025	3 1/2"	25
	RWA-40025	4"	25

Inside Diameter		Outer Diameter	
Min	Max	Min	Max
0.374	0.392	0.559	0.609
0.374	0.392	0.559	0.609
0.625	0.644	0.859	0.920
0.811	0.835	1.044	1.105
1.000	1.040	1.300	1.379
1.250	1.300	1.550	1.629
1.500	1.573	1.850	1.950
2.000	2.079	2.350	2.450
2.500	2.700	2.859	3.059
3.000	3.200	3.359	3.559
3.500	---	3.859	4.059
4.000	---	4.359	4.559